

国标型号	国际标型号	频率范围 (GHz)	内截面尺寸		宽和高 偏差 c	外截面尺寸		每米重量 (Kg)	
			宽度 a	高度 b		宽度 a1	高度 b1	铜波导	铝波导
BJ14	WR650	1.13~ 1.73	165.10	82.55	0.33	169.16	86.61	9.10	2.79
BJ18	WR510	1.45~ 2.20	129.54	64.77	0.26	133.60	68.83	7.17	2.20
BJ22	WR430	1.72~ 2.61	109.22	54.61	0.22	113.28	58.67	6.07	1.86
BJ26	WR340	2.17~ 3.30	86.36	43.18	0.17	90.42	47.24	4.83	1.46
BJ32	WR284	2.60~ 3.95	72.14	34.04	0.14	76.20	38.10	3.98	1.22
BJ40	WR229	3.22~ 4.90	58.17	29.08	0.12	61.42	32.33	2.62	0.80
BJ48	WR187	3.94~ 5.99	47.549	22.149	0.095	50.80	25.40	2.11	0.65
BJ58	WR159	4.64~ 7.05	40.386	20.193	0.081	43.64	23.44	1.85	0.57
BJ70	WR137	5.38~ 8.17	34.849	15.799	0.070	38.10	19.05	1.56	0.48
BJ84	WR112	6.57~ 9.99	28.499	12.624	0.057	31.75	15.88	1.28	0.39
BJ100	WR90	8.20~ 12.5	22.860	10.16	0.046	25.40	12.70	0.80	0.25
BJ120	WR75	9.84~ 15.0	19.050	9.525	0.038	21.59	12.06	0.70	0.22
BJ140	WR62	11.9~ 18.0	15.799	7.899	0.031	17.83	9.93	0.47	0.14
BJ180	WR51	14.5~ 22.0	12.954	6.477	0.026	14.99	8.51	0.39	0.12
BJ220	WR42	17.6~ 26.7	10.668	4.318	0.021	12.70	6.35	0.31	0.09
BJ260	WR34	21.7~ 33.0	8.636	4.318	0.020	10.67	6.35	0.27	0.08
BJ320	WR28	26.3~ 40.0	7.112	3.556	0.020	9.14	5.59	0.23	0.07

BJ400	WR22	32.9~ 50.1	5.690	2.845	0.020	7.72	4.88	0.20	0.06
BJ500	WR18	39.2~ 59.6	4.775	2.388	0.020	6.81	4.42	0.17	0.05
BJ620	WR14	49.8~ 75.8	3.759	1.880	0.020	5.79	3.91	0.14	0.04
BJ740	WR12	60.5~ 91.9	3.0988	1.5494	0.0127	5.13	3.58	0.12	0.037
BJ900	WR10	73.8~ 112	2.5400	1.2700	0.0127	4.57	3.30	0.11	0.032